

SINGLE OR MULTIPLE MOTOR.  
ALWAYS A CLEAN PERFORMANCE.

	SW 32IP	SW 30IP	SW 30IS	SW 50IP	SW 50IS
L x B x H	430x360x580 mm	450x450x820 mm	430x430x830 mm	570x570x1030 mm	520x520x960 mm
Working width	400 mm	400 mm	400 mm	400 mm	400 mm
Suction hose	2,5 m	2,5 m	2,5 m	2,5 m	2,5 m
Tank capacity	30 l	35 l	32 l	72 l	62 l
Noise level	70 dB(A)	73,4 dB(A)	73,4 dB(A)	73,4 dB(A)	73,4 dB(A)
Weight	7,8 kg	13 kg	13 kg	20 kg	19 kg

ELECTRCAL DATA

Rated voltage	230 V	230 V	230 V	230 V	230 V
Power max.	1300 W	1200 W	1200 W	1200 W	1200 W
Mains cable	10 m	12 m	12 m	12 m	12 m

SUCTION MOTOR

Low pressure, max.	260 mbar	240 mbar	240 mbar	240 mbar	240 mbar
Air flow, max.	56 l/s	58 l/s	58 l/s	58 l/s	58 l/s
Number of motors	1	1	1	1	1

	SW 52IP	SW 52IS	SW 53IP	SW 53IS
L x B x H	650x590x1050 mm	650x590x1050 mm	650x590x1050 mm	650x590x1050 mm
Working width	400 mm	400 mm	400 mm	400 mm
Suction hose	2,5 m	2,5 m	2,5 m	2,5 m
Tank capacity	72 l	78 l	72 l	78 l
Noise level	80,5 dB(A)	80,5 dB(A)	81,5 dB(A)	81,5 dB(A)
Weight	29,5 kg	30 kg	32 kg	32,5 kg

ELECTRCAL DATA

Rated voltage	230 V	230 V	230 V	230 V
Power max.	2400 W	2400 W	3300 W	3300 W
Mains cable	12 m	12 m	12 m	12 m

SUCTION M OTOR

Low pressure, max.	240 mbar	240 mbar	240 mbar	240 mbar
Air flow, max.	116 l/s	116 l/s	175 l/s	175 l/s
Number of motors	2	2	3	3

Technical data subject to change without notice.

G. Staehle GmbH u. Co. KG  
Mercedesstr. 15, D 70372 Stuttgart  
Telefon +49 (0)7 11/95 44 - 960  
Telefax +49 (0)7 11/95 44 - 941  
export@columbus-clean.com  
www.columbus-clean.com

CLEAN IS QUALITY **columbus**

WET AND DRY VACUUM CLEANER.  
30 UP TO 78 LITRES.



70022202 | 2015/1

CLEAN IS QUALITY **columbus**

## CLEANING ON THE MOVE: THE HIGH SUCTION COMPACT CLASS.

### SW 32IP

### SW 30IP

### SW 30IS

### SW 50IP

### SW 50IS

Well equipped for basic cleaning, initial construction cleaning or use in workshops: wet & dry vacuum cleaners with compact vacuum tanks made of impact-resistant plastic (P) or chromium steel (S).

Robust and sturdy design: secure positioning and convenient transport every time.

Extensive range of professional accessories: a roller-guided wet suction tool as well as additional accessories for dry and wet cleaning are series-standard and included in delivery. A large assortment of special extras is also available.

Hygienic dry cleaning: the specially pre-treated sanifilter cloth bag – series-standard for the SW 30 to SW 53 wet and dry vacuum cleaners – prevents the growth of bacteria, viruses, fungi (yeasts and mould) and microparasites that have been vacuumed up.

#### SW 32IP

Versatile and ergonomic: the introductory model for enjoyable work. The wet and dry vacuum cleaner's light weight allows easy and flexible use on small and medium-sized surfaces.

Not only for vacuuming: with the integrated blower function, it is easy to blow out filters and filter baskets as well as dust and dirt particles from work benches or to blow dry surfaces.

#### SW 30IP

#### SW 30IS

The handy, compact and mobile single-motor all-rounder with 32 or 35-litre tank capacity for professional use on small surfaces.

#### SW 50IP

#### SW 50IS

The single-motor expert for longer operating times without emptying the tank: 62 or 72-litre capacity for medium to large surfaces.

Easy to empty: the drain hose situated at the lowest point of the tank allows the dirty water to be emptied completely and conveniently.

## CLEAN DESIGN: THE PROFESSIONAL CLASS FOR THE TOUGHEST TASKS.

### SW 52IP

### SW 52IS

### SW 53IP

### SW 53IS

Real professionals: the SW 52 wet and dry vacuum cleaner with two motors and the SW 53 with three for medium to large surfaces.

Strong suction – wet or dry: for impressive results for a variety of hose lengths, the motors can be switched on and off individually.

Coarse dirt is easy: the powerful suction capacity in connection with robust and high-quality vacuum hoses with a diameter of 38 mm allow even larger debris to be vacuumed up easily.

Quick and clean: thanks to the ample tank with 72 and 78 litres, both models can vacuum up large amounts of dirt and liquid with ease. The vacuum tanks can be emptied quickly and conveniently using the tilting device or the drain hose.

